

ResQ® RAFT-10

SPECIFICATION SHEET



The ResQ® RAFT-10 is a lightweight, rapid deployment raft specifically designed to engage in challenging flood and water rescue evacuations. Featuring enlarged sponsons, the raft allows a larger payload allowance whilst maintaining stability during application. Leaflet valves installed on the deck/sponsons ensure inflation/deflation is effortless, whilst over-inflation is prevented via a Pressure Relief Valve (PRV) safety system. Transportation of the ResQ® Raft is simple via integrated handles when inflated or via a stowage valise when fully deflated. The ResQ® RAFT-10 is also available in the following variants; RAFT-15.

STANDARD FEATURES*:

Material:	Hypalon	Air Volume	1500L
Length overall:	3.00m	Packed Dimensions:	0.80m x 0.60m x 0.50m
Beam Overall:	2.00m	Paddles:	2
Weight:	45kg	Soft Valise:	Yes
Load Capacity:	950kg	Inflation Hand Pump:	Yes
Persons:	10	Repair Kit:	Yes

*Specification information may be subject to change in accordance with © Specialised Inflatable Technology Limited's continuous line of improvement policy.

OPTIONAL FEATURES:

Colour

Signwriting

Rapid Inflation Kit



SPECIALISED INFLATABLE TECHNOLOGY LTD

112 Clydesdale Place, Moss Side Ind Est, Leyland, Preston, PR26 7QS, UK

Tel: +44 (0) 1772 459143 Email: sales@sitltd.co.uk Website: www.sitltd.co.uk